

# Cam Lever Couplings

- Precision moulded glass reinforced polypropylene
  - EPDM gaskets, 316 S/Steel arms, rings & pins
  - Suitable for many acids & aggressive chemicals \*
- Operating conditions & pressures:  
 3/8" to 2" = 6.4 Bar @ -17.8°C 8.6 Bar @ 21.2°C 4.8 Bar @ 47.8°C  
 3" to 4" = Cap max press 3.4 Bar - Couplings max press 5 Bar

\*This information is for guidance only. Contact our sales office for further assistance on chemical compatibility

1/2" & 3/4" couplings and adapters are compatible - 1 1/4" & 1 1/2" couplings and adapters are compatible

## Female Coupler



Part No.	Thread	Code
050DP	1/2"	L
075DP	3/4"	L
100DP	1"	L
125DP	1 1/4"	L
150DP	1 1/2"	L
200DP	2"	L
300DP	3" (NPT)	L
300DPBSP	3" (BSP)	L

## Female Adapter



Part No.	Thread	Code
050AP	1/2"	L
075AP	3/4"	L
100AP	1"	L
125AP	1 1/4"	L
150AP	1 1/2"	L
200AP	2"	L
300AP	3" (NPT)	L
300APBSP	3" (BSP)	L

## Male Coupler



Part No.	Thread	Code
050BP	1/2"	L
075BP	3/4"	L
100BP	1"	L
125BP	1 1/4"	L
150BP	1 1/2"	L
200BP	2"	L
300BP	3" (NPT)	L
300BPBSP	3" (BSP)	L

## Coupler Cap



Part No.	Size	Code
075CAPP	3/4"	L
100CAPP	1"	L
150CAPP	1 1/2"	L
200CAPP	2"	L
300CAPP	3"	L
400CAPP	4"	L

## Adapter Plug



Part No.	Size	Code
075PLP	3/4"	L
100PLP	1"	L
150PLP	1 1/2"	L
200PLP	2"	L
300PLP	3"	L
400PLP	4"	L

Plug 150PLP fits 1 1/4" couplings

## Hose Adapter



Part No.	Barb	Code
050EP	1/2"	L
075EP	3/4"	L
100EP	1"	L
125EP	1 1/4"	L
150EP	1 1/2"	L
200EP	2"	L
300EP	3"	L
400EP	4"	L

## Hose Coupler



Part No.	Barb	Code
050CP	1/2"	L
075CP	3/4"	L
100CP	1"	L
125CP	1 1/4"	L
150CP	1 1/2"	L
200CP	2"	L
300CP	3"	L
400CP	4"	L

## Male Adapter



Part No.	Thread	Code
050FP	1/2"	L
075FP	3/4"	L
100FP	1"	L
125FP	1 1/4"	L
150FP	1 1/2"	L
200FP	2"	L
300FP	3" (NPT)	L
300FPBSP	3" (BSP)	L

## 90° Female Adapter



Part No.	Thread	Code
150A-90	1 1/2" F	L
200A-90	2" F	L

## 90° Hose Coupler



Part No.	Barb	Code
150C-90	1 1/2"	L
200C-90	2"	L